

Technical Data Sheet MOY SA Primer L

Product Description / Uses:

MOY SA Primer L has been specifically developed to improve the adhesion of self-adhered air and vapour control layers (AVCL's) to roof decks. MOY SA Primer L is a roller-applied, solvent-based synthetic-rubber bonding agent that offers the roofing manufacturer and contractor many benefits.

Maybe applied to a range of surfaces*:

- Concrete
- Timber
- Brickwork
- Metals – mild steel, zinc & lead
- Slate, lightweight concrete screeds

Coverage Rates:

3-8 metres per litre, dependent on substrate porosity.

Method of Application:

MOY SA Primer L can be applied by brush or roller.

Application Instructions:

- Ensure all surfaces to be bonded are clean, dry and free from contamination.
- Metal surfaces should be degreased and any flaking paint and corrosion removed.
- MOY SA Primer L is supplied ready to use. Apply a thin even layer using a brush/roller or spray.
- Allow to dry before applying the self-adhesive membranes.
- Apply the self-adhesive membranes as per manufacturer's specifications and consolidate with a 20kg water filled roller.
- Drying times may vary depending on ambient temperature, coating thickness and porosity of the substrates. MOY SA Primer L can be used for up to 4 hours after application (20°C). If this time is exceeded, recoat the substrate.

Cleaning Tools:

Tools may be cleaned with White Spirit. Minor spillages should be wiped off surfaces immediately before the product has set.

Packaging:

5.5kg or 12.5kg tins.

Storage Conditions:

The product should be stored unopened in a dry condition at a temperature of 5-25°C. This will ensure the stated shelf-life. The adhesive will have a limited life once the container is opened.



Technical Data Sheet MOY SA Primer L

Limitations:

- Do not use in temperatures less than +5°C.
- It is the user's responsibility to ensure suitability for use. Safety Data Sheet available on request.
- Read the label carefully for essential health and safety information prior to use.

Technical Specification:

Base	Synthetic Rubber
Colour	Black.
Temperature Resistance	-30°C to 90°C
Coverage**	3-8m ² /L
Application Temperature	5°C - 30°C
Viscosity @ 20°C	900cps
Drying Time @ 20°C***	Approx. 15 minutes
Working Time	Up to 4 hours
Shelf Life	12 months
Storage	5°C - 25°C
Health & Safety	See SDS
Cleaner	Solvent 7

* Adhesion tests should be carried out prior to use.

** Coverage stated is approximate and dependant on porosity and type of substrate (two coats may be required on very porous substrates).

*** Drying times can vary depending on temperature fluctuations.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact MOY Technical Services.